



cnPilot R190V for ISPs

Cloud managed Home Router with ATA

The IPV6 capable R190V is ideal for cost-conscious service providers seeking a standard, entry level home router with cutting edge cloud management and robust features. The R190V can be remotely configured, monitored, and upgraded, and offers in-home client insights that make troubleshooting a breeze – all reducing the ISP’s need for site visits.



cnPilot R190V

MAKING THE CASE - RETURN ON INVESTMENT (ROI)

It’s estimated that over 60% of customer complaint calls to service providers (SPs) for “poor internet service” result from unmanaged home routers, purchased and deployed by end customers themselves.

Service providers lose money servicing these complaints with no visibility to the indoor home router, with no improvement in customer satisfaction, high subscriber churn, or ability to recover lost revenue opportunities. The R190V gives service providers more options than ever, enabling them to:

- Enhance customer satisfaction by offering standardized SP- validated and managed indoor home routers that connect users to the internet rapidly and efficiently.
- Sell or lease the R190V as the ISP provided and managed home router. The ATA port enables ISPs to provide Voice-over-IP phone service, creating a new line of revenue for the ISPs
- Reduce service call costs with client visibility via cnMaestro with the ezView tool. Track and manage customer inventory, and see attached clients and RSSI information remotely – enabling fast customer support.

REMOTE CLOUD OR ON-PREMISES MANAGED

The cnPilot R190V solution can be deployed with Cambium’s cnMaestro cloud controller or On-premises controller versions, offering:

- Zero touch onboarding
- Inventory tracking and monitoring
- Dashboard views with alarms
- Remote mass upgrade
- TR-069 & SNMP management

ezVIEW: TROUBLESHOOTING

With ezView, cnMaestro offers rich client and device troubleshooting capabilities integrated with ongoing management. When backhauled wirelessly, ezView’s single-pane-of-glass display shows data from clients, the Wi-Fi router (R190V), and the ePMP or PMP 450 wireless links backhauling the router.

IPV4 & IPV6 – FOR TODAY AND TOMORROW

The R190V supports modern IPV6 network topology

LICENSE-FREE ROUTER. ONE LOW PRICE.

SPECIFICATIONS

VoIP SoC	<ul style="list-style-type: none"> MIPS Single-core 580MHz 		
Flash	<ul style="list-style-type: none"> 16MBytes Flash 		
RAM	<ul style="list-style-type: none"> 64MBytes DDR3 RAM 		
CPU	<ul style="list-style-type: none"> MT7628 		
Power Supply	<ul style="list-style-type: none"> AC/DC Adapter AC Input: 100-240V, 50-60Hz DC Output: 12V, 1.0A 		
I/O Interfaces	<ul style="list-style-type: none"> 1 RJ-45 for WAN port (Ethernet 100 Base-T) 3 RJ-45 for LAN port (Ethernet 100 Base-T) 2 RJ-11 for FXS port IEEE802.11 b/g/n 		
Environmental	<ul style="list-style-type: none"> Operation Temperature: -5-45 Degree C Storage Temperature: -25- 85 Degree C Relative Humidity: 10%-90% No Condensing 		
Key Feature	<ul style="list-style-type: none"> 100Mbps NAT/NAPT speed 2T2R 2.4G 802.11 b/g/n(300 Mbps) Support VoIP FXS port with SIP and T.38 FAX 		
Audio Codec	<ul style="list-style-type: none"> G.711 (A-Law, u-Law) with PESQ above 4.3 G.729 with PESQ above 3.7 Adaptive Jitter Buffer Management Voice Activity Detection Comfort Noise Generation Echo Cancellation T.30 FAX with G.711 Real time FAX over IP via T.38 		
Wireless	<ul style="list-style-type: none"> 802.11 b/g/n support 4 SSID Static WEP(64/128bit) Dynamic WEP(64/128bit) AES(CCMP/TKIP) MAC certification WEP certification WPA-PAK/WPA-PSK(2.0) WPA/WPA2 AP Isolation and MBSSID AP Isolation WMM WDS WPS Station list Wireless MAC Filter 		
		Applications	<ul style="list-style-type: none"> NAT mode and Bridge mode Support DDNS MAC address cloning SIP proxy redundancy NAT Traversal by STUN Built-in Wired speed NAT Router DHCP Server and Client IP conflict detection Port Forwarding, DMZ, SuperDMZ 802.1Q VLAN/802.1p, DSCP, Rate Limiting VPN(PPTP,L2TP, IPSec) Passthrough SNTP IGMPv2 Firewall(SYN Flooding, IP Spoofing, Smurf Attack, Ping of Death, DoS)
		Management	<ul style="list-style-type: none"> Firmware Upgrade Web Management Interface IVR-driven Management Interface Local and Remote Syslog (RFC3164) Auto Provisioning SNTP Time Synchronization Multi User Level SNMP v2 Telnet TRO69 System Log: local log and remote log
		Call Features	<ul style="list-style-type: none"> 3-way conference Call hold Call forwarding Call Transfer Call waiting Caller ID and CWCID DTMF Relay: In-band, Out-band and SIP INFO QoS Layer 3 Call Log CID/CWCID Dial Plan DTMF Mode: Inband, outband and SIP Info