


UniFi® Protect



UniFi Protect G4 Dome Camera



UniFi Protect G4 Dome security camera features 4 MP video performance, two-way audio, and a weather-resistant enclosure for discreet surveillance, indoors, or outdoors. Infrared LEDs and an automatic IR cut filter allow for a day or night monitoring.

Mechanical

Dimensions	Ø109.2 x 64.5 mm (Ø4.3 x 2.5")
Weight	Without Mount: 370 g (13.05 oz) With Mount: 390 g (13.76 oz)
Enclosure Materials	Aluminum Alloy, Polycarbonate, Hard-Coated Dome
Mounting Materials	Polycarbonate, Stainless Steel
Weatherproofing	IPX4
Resistance	IK08

Optics

Sensor	5 MP CMOS Sensor
Lens	Fixed Focal Length
View Angle	H: 86°, V: 60°, D: 111°
Night Mode	Built-in Light Sensor Built-in IR LED Illumination and IR Cut Filter

Video

Video Compression	H.264
Resolution	2688 x 1512 (16:9)
Maximum Frame Rate	24 FPS
Image Settings	Brightness, Contrast, Sharpness, Saturation, Noise Reduction, 50/60 Hz

System

Processor Specs	Ambarella Advanced Image Processing SoC
Memory Information	512 MB
Management Interface	UniFi Protect
Networking Interface	RJ45, 10/100/1000 Mbps Ethernet
Flash Memory Support	256 MB
Max. Power Consumption	5W
Power Method	802.3af PoE, 44-57VDC, 0.114-0.088A
Supported Voltage Range	44-57VDC
Link/Activity LED	Yes
Button	Factory Reset
Operating Temperature	-20 to 40° C (-4 to 104° F)



Operating Humidity	0 to 90% Noncondensing
--------------------	------------------------

Certifications	FCC, IC, CE
----------------	-------------

Audio

Microphone	Yes (Can be Disabled in Software)
------------	-----------------------------------

Speaker	Yes
---------	-----

Software

Controller Software	UniFi Protect
---------------------	---------------

Mobile Apps	UniFi Protect iOS and Android
-------------	-------------------------------

